## NSN 3020-01-115-2817

Spur Antibacklash Gear - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/3020-01-115-2817 **Attachment Method:** Mounting hole Pitch Diameter: 2.6875 inches **Teeth Quantity:** 172 **Bore Style:** Plain both ends **Mounting Hole Thread Series Designator:** Unc transversely through hub, first end Mounting Hole Thready Qty Per Inch (tpi): 56 transversely through hub, first end **Mounting Hole Thread Size:** 0.086 inches transversely through hub, first end **Mounting Hole Type And Quantity:** 1 threaded transversely through hub, first end **Outside Diameter:** 2.7190 inches **Tooth Form:** Standard **Pressure Angle:** 20.0000 degrees Distance Between Body Face And Protruding Hub End: 0.281 inches first end **Face Width:** 0.104 inches **Bore Diameter:** 0.250 inches both ends **Hub Style Designator:** 1 step first end **End Length:** 0.250 inches first end **Precision Classification:** Quality number 10 **End Diameter:** 0.500 inches first end First Step Length: 0.031 inches first end First Step Diameter: 0.438 inches first end

Material:

Steel comp 303

## NSN 3020-01-115-2817

No Fiig: A27300

Spur Antibacklash Gear - Page 2 of 2



Material Specification:
Qq-s-764, type 303 federal specification single material response
Surface Treatment:
Passivate hub
Surface Treatment Specification:
Qq-p-35, type 1 federal specification single treatment response
Style Designator:
Protruding hub
Shelf Life:
N/a
Unit Of Measure:
Demilitarization: