NSN 3020-01-115-4356



Spur Antibacklash Gear - Page 1 of 2 View Online at https://aerobasegroup.com/nsn/3020-01-115-4356 **Pitch Diameter:** Between 1.3271 inches and 1.3281 inches **Teeth Quantity:** 85 **Bore Style:** Plain both ends **Backlash Designation:** Grade c **Outside Diameter:** 1.359 inches **Tooth Form:** Standard **Pressure Angle:** 20.0000 degrees **Distance Between Body Face And Protruding Hub End:** 0.281 inches first end **Face Width:** 0.104 inches **Bore Diameter:** 0.125 inches both ends **Hub Style Designator:** Pinned first end **Hub Diameter:** 0.310 inches first end **Precision Classification:** Quality number 10 **Special Features:** Mtg holes 90 degrees apart Material: Steel comp 303 **Material Specification:** Qq-s-764, type 303 federal specification single material response **Surface Treatment: Passivate Surface Treatment Specification:** Qq-p-35, type 2 federal specification single treatment response

Style Designator:

Protruding hub

Furnished Items And Quantity:

1 setscrew

Shelf Life:

N/a

NSN 3020-01-115-4356

Spur Antibacklash Gear - Page 2 of 2



			ure:	

--

Demilitarization:

No

Fiig:

A27300