## NSN 3020-01-115-5254

Spur Antibacklash Gear - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/3020-01-115-5254

Attachment Method:					
Clamp					
Pitch Diameter:					
Between 2.3428 inches and 2.3438 inches					
Teeth Quantity:					
150					
Bore Style:					
Plain both ends					
Outside Diameter:					
2.3750 inches					
Tooth Form:					
Standard					
Pressure Angle:					
20.0000 degrees					
Distance Between Body Face And Protruding Hub End:					
0.281 inches first end					
Face Width:					
0.104 inches					
Bore Diameter:					
0.125 inches both ends					
Hub Style Designator:					
1 step first end					
End Length:					
0.250 inches first end					
Precision Classification:					
Quality number 12					
End Diameter:					
0.188 inches first end					
First Step Length:					
0.031 inches first end					
First Step Diameter:					
0.312 inches first end					
Material:					
Steel comp 303 hub					
Material Specification:					
Qq-s-764 federal specification single material response hub					
Surface Treatment:					
Passivate hub					
Surface Treatment Specification:					
Qq-p-35, type 1 federal specification single treatment response hub					
Style Designator:					
Protruding hub					

## NSN 3020-01-115-5254

Spur Antibacklash Gear - Page 2 of 2



-			 
٠.	hΔ	Iŧ.	ife:

N/a

**Unit Of Measure:** 

--

Demilitarization:

No

Fiig:

A27300