## NSN 3020-01-116-7716

Spur Gear - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/3020-01-116-7716

Body Style:
Webbed, solid
Attachment Method:
Mounting hole
Pitch Diameter:
1.0000 inches
Teeth Quantity:
96
Bore Style:
Plain both ends
Mounting Hole Type And Quantity:
2 threaded axially through flange
Outside Diameter:
1.020 inches
Tooth Form:
Standard
Pressure Angle:
20.0000 degrees
Distance Between Body Face And Protruding Hub End:
0.221 inches first end
Face Width:
0.045 inches
Bore Diameter:
0.090 inches both ends
Hub Style Designator:
1 groove first end
Hub Diameter:
0.249 inches first end
First Groove Width:
0.029 inches first end
First Groove Diameter:
0.210 inches first end
Distance From End To First Groove:
0.148 inches first end
Material:
Steel comp 303
Material Specification:
Mil-s-7720, comp 303, cond a military specification single material response
Surface Treatment:
Passivate

\_ \_ \_

**Surface Treatment Specification:** 

Mil-std-171, finish no. 5.4.1 military standard single treatment response

## NSN 3020-01-116-7716

Spur Gear - Page 2 of 2



Style Designator:
Protruding hub
Shelf Life:
N/a
Unit Of Measure:
 Demilitarization:
Demilitarization:

Mil-std (military Standard):

Mil-s-7720 spec.