NSN 3020-01-117-0334

Helical Antibacklash Gear - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/3020-01-117-0334 Pitch Diameter: 6.2000 inches **Teeth Quantity:** 124 **Bore Style:** 10a w/ keyway both ends **Hardness Rating:** 27.0 rockwell c and 32.0 rockwell c **Outside Diameter:** 6.300 inches **Teeth Type:** Single helix **Tooth Form:** Standard **Tooth Direction:** Left **Pressure Angle:** 20.0000 degrees **Helix Angle:** 15.0000 degrees **Distance Between Body Face And Protruding Hub End:** 0.336 inches first end **Face Width:** 0.380 inches **Bore Diameter:** 0.957 inches both ends **Keyway Width:** 0.156 inches both ends **Distance From Bore Center To Keyway Bottom:** 0.518 inches both ends **Hub Style Designator:** Pinned first end **Hub Diameter:** 1.499 inches first end **Precision Classification:** Quality number 12 or quality number 13 Material: Steel comp 4140 or steel comp 4140h

Material Specification:

66 federal standard 1st material response or mil-s-890 military specification 2nd material response

Surface Treatment:

Oxide

NSN 3020-01-117-0334

Helical Antibacklash Gear - Page 2 of 2



Surface Treatment Specification:

Mil-c-13924, cl 1 military specification single treatment response

Style Designator:

Protruding hub

Shelf Life:

N/a

Unit Of Measure:

__

Demilitarization:

Yes - demil/mli

Fiig:

A27300

Mil-std (military Standard):

Mil-s-890 spec.