NSN 3020-01-118-7528

Spur Gear - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/3020-01-118-7528

Body Style:
Webbed, offset, solid
Attachment Method:
Mounting hole
Pitch Diameter:
12.0000 inches
Teeth Quantity:
120
Bore Style:
W/counterbore both ends
Mounting Hole Thread Series Designator:
Unc axially through body, first end
Mounting Hole Thready Qty Per Inch (tpi):
16 axially through body, first end
Mounting Hole Thread Size:
0.375 inches axially through body, first end
Mounting Hole Type And Quantity:
2 plain axially through body, first end and 2 threaded axially through body, first end
Outside Diameter:
12.200 inches
Tooth Form:
Standard
Pressure Angle:
20.0000 degrees
Distance Between Body Face And Protruding Hub End:
1.937 inches second end
Body Recess Depth:
2.875 inches first end
Face Width:
1.062 inches
Bore Diameter:
6.250 inches counterbore, first end
Counterbore Depth:
0.313 inches first end
Counterbore Diameter:
9.251 inches counterbore, first end
Hub Style Designator:
Plain second end
Hub Diameter:
7.250 inches second end
Mounting Hole Diameter:
0.078 inches axially through body, first end

NSN 3020-01-118-7528

Spur Gear - Page 2 of 2

Mil-std (military Standard):

Mil-m-16576 spec.



Bolt Hole Circle Diameter:
8.250 inches axially through body, first end
Material:
Copper alloy 903
Material Specification:
Mil-m-16576 military specification single material response
Style Designator:
Cone shape body, protruding hub
Shelf Life:
N/a
Unit Of Measure:
Demilitarization:
No
Fiig:
A27300