

View Online at <https://aerobasegroup.com/nsn/3020-01-121-0173>

Groove Depth:

1.344 inches

Groove Width:

0.438 inches

Outside Diameter:

8.570 inches

Overall Length:

2.000 inches

Keyway Width:

Between 0.188 inches and 0.190 inches

Thread Size:

3/8-24

Bore Diameter:

Between 0.877 inches and 0.882 inches

Bore Length:

2.000 inches

Distance From Center Of Bore To Bottom Of Keyway:

0.015 inches

V Groove Angle In Deg:

36.0

Pitch Diameter:

7.000 inches and 8.000 inches

Securing Hole Quantity:

1

Material And Location:

Aluminum alloy, qq-a-601, alloy 356 or aluminum alloy, qq-a-596, alloy 356, t6 or aluminum alloy, qq-a-367, t6

Face Width:

1.375 inches

Design Form:

Webbed

Bore Type:

Straight

Bearings:

Not included

Groove Quantity:

2

Counterbore Feature:

Not included

Hole Location:

Center 0.375 in. From hub end

Keying Facility:

Included

Keying Facility Type:

Keyway

Securing Method:

Threaded hole

Split Hub Feature:

Included

Lightening Hole:

Not included

Integral Cooling Vane:

Not included

Groove Shape:

V

Bore Feature:

Included

Protruding Hub Characteristic:

Plain

Hub Split Location:

Through one wall

Clamping Bolt Quantity:

1

Securing Location:

Aa end

Hub End Outside Diameter And Location:

2.625 inches both ends

Distance From Outside Flange/rim To Hub End And Location:

0.625 inches aa end

Quantity:

1

Surface Treatment:

Anodize

Style Designator:

Webbed or spoked

Surface Treatment:

Anodized aluminum

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

T353-a