NSN 3020-01-121-6428

Spur Gear - Page 1 of 2

Plain, solid



View Online at https://aerobasegroup.com/nsn/3020-01-121-6428

Body Style:

Attachment Method: Mounting hole Pitch Diameter: 7.5000 inches **Teeth Quantity:** 120 **Bore Style:** 10a w/ keyway both ends **Mounting Hole Thread Series Designator:** Unc axially through body, first end Mounting Hole Thready Qty Per Inch (tpi): 16 axially through body, first end **Hardness Rating:** 34.0 rockwell c and 38.0 rockwell c **Mounting Hole Thread Size:** 0.375 inches axially through body, first end **Mounting Hole Type And Quantity:** 3 threaded axially through body, first end **Outside Diameter: 7.625** inches **Tooth Form:** Standard **Pressure Angle:** 20.0000 degrees **Distance Between Body Face And Protruding Hub End:** 0.1875 inches first end **Face Width:** 0.438 inches **Bore Diameter:** 2.937 inches both ends **Keyway Width:** 0.250 inches both ends **Distance From Bore Center To Keyway Bottom:** 1.593 inches both ends **Hub Style Designator:** Plain both ends **Hub Diameter:** 4.000 inches first end **Bolt Hole Circle Diameter:**

5.500 inches axially through body, first end

NSN 3020-01-121-6428

Spur Gear - Page 2 of 2

No Fiig: A27300



Material:
Steel comp 4340
Material Specification:
Fed standard 66 federal standard single material response
Style Designator:
Protruding hubs
Shelf Life:
N/a
Unit Of Measure:
Demilitarization: