## NSN 3020-01-121-6428

Spur Gear - Page 1 of 2





**Body Style:** 

Plain, solid

**Attachment Method:** 

Mounting hole

## **Pitch Diameter:**

7.5000 inches

## **Teeth Quantity:**

120

#### Bore Style:

10a w/ keyway both ends

#### Mounting Hole Thread Series Designator:

Unc axially through body, first end

#### Mounting Hole Thready Qty Per Inch (tpi):

16 axially through body, first end

#### Hardness Rating:

34.0 rockwell c and 38.0 rockwell c

#### Mounting Hole Thread Size:

0.375 inches axially through body, first end

## Mounting Hole Type And Quantity:

3 threaded axially through body, first end

## **Outside Diameter:**

7.625 inches

Tooth Form:

Standard

#### Pressure Angle:

20.0000 degrees

### Distance Between Body Face And Protruding Hub End:

0.1875 inches first end

#### Face Width:

0.438 inches

#### Bore Diameter:

2.937 inches both ends

#### Keyway Width:

0.250 inches both ends

#### Distance From Bore Center To Keyway Bottom:

1.593 inches both ends

## Hub Style Designator:

Plain both ends

#### **Hub Diameter:**

4.000 inches first end

#### **Bolt Hole Circle Diameter:**

5.500 inches axially through body, first end

# NSN 3020-01-121-6428

Spur Gear - Page 2 of 2



Material:

Steel comp 4340

## Material Specification:

Fed standard 66 federal standard single material response

## Style Designator:

Protruding hubs

Shelf Life:

N/a

Unit Of Measure:

--

## Demilitarization:

No

## Fiig:

A27300