## NSN 3020-01-123-2122

Spur Gear - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/3020-01-123-2122 **Body Style:** Plain, solid **Attachment Method:** Mounting hole Pitch Diameter: 0.7500 inches **Teeth Quantity:** 72 **Bore Style:** Plain both ends **Mounting Hole Thread Series Designator:** Unc transversely through hub, first end **Mounting Hole Thread Size:** 0.086 inches transversely through hub, first end **Mounting Hole Type And Quantity:** 1 threaded transversely through hub, first end **Outside Diameter:** 0.771 inches **Tooth Form:** Standard **Pressure Angle:** 20.0000 degrees Distance Between Body Face And Protruding Hub End: 0.187 inches first end **Face Width:** 0.125 inches **Bore Diameter:** 0.125 inches both ends **Hub Style Designator:** Pinned first end **Hub Diameter:** 0.312 inches first end Material: Steel comp 303s or steel comp 303 **Material Specification:** Mil-s-7720 military specification 1st material response or qq-s-764, cond a federal specification 2nd material response **Surface Treatment:** 

**Passivate** 

**Surface Treatment Specification:** 

Qq-p-35, type 1 federal specification single treatment response

**Style Designator:** 

Protruding hub

## NSN 3020-01-123-2122

Spur Gear - Page 2 of 2



N/a
Unit Of Measure:
Demilitarization:
No
Fiig:
A27300

Mil-std (military Standard):

Mil-s-7720 spec.

Shelf Life: