## NSN 3020-01-124-2809

Spur Gear - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/3020-01-124-2809 **Body Style:** Plain, solid **Attachment Method:** Mounting hole Pitch Diameter: 0.4500 inches **Teeth Quantity:** 90 **Bore Style:** Plain both ends **Backlash Designation:** Grade b **Mounting Hole Thread Series Designator:** Unf transversely through hub, first end Mounting Hole Thready Qty Per Inch (tpi): 72 axially through body, second end **Mounting Hole Thread Size:** 0.073 inches transversely through hub, first end **Mounting Hole Type And Quantity:** 1 threaded transversely through hub, first end **Outside Diameter:** 0.460 inches **Tooth Form:** Standard **Pressure Angle:** 20.0000 degrees **Distance Between Body Face And Protruding Hub End:** 0.120 inches first end **Face Width:** 0.060 inches **Bore Diameter:** 0.047 inches both ends **Hub Style Designator:** Pinned first end **Hub Diameter:** 0.175 inches first end **Precision Classification:** Quality number 10 Material: Copper alloy 342 **Material Specification:** 

Qq-b-613, 1/2h federal specification single material response

## NSN 3020-01-124-2809

Spur Gear - Page 2 of 2



| •     |          |       |
|-------|----------|-------|
| StVID | l Jacian | ator. |
| OLYIC | Design   | atoi. |

Protruding hub

Shelf Life:

N/a

**Unit Of Measure:** 

--

Demilitarization:

No

Fiig:

A27300