

View Online at <https://aerobasegroup.com/nsn/3020-01-124-7963>

Counterbore Diameter:

Between 5.501 inches and 5.503 inches

Counterbore Depth:

0.310 inches

Groove Depth:

0.380 inches

Groove Width:

0.312 inches

Outside Diameter:

9.750 inches

Overall Length:

3.090 inches

Bolt Circle Diameter:

4.876 inches

Thread Size:

5/16-24

Bore Length:

3.090 inches

V Groove Angle In Deg:

40.0

Securing Hole Quantity:

6

Taper Bore Major Diameter:

1.500 inches

Taper Bore Minor Diameter:

1.369 inches

Material And Location:

Iron, ductile

Face Width:

1.530 inches

Design Form:

Webbed

Bore Type:

Tapered

Bearings:

Not included

Groove Quantity:

3

Counterbore Feature:

Included

Counterbore Location:

Bb end

Hole Location:

Thru pulley surface

Keying Facility:

Not included

Securing Method:

Threaded hole

Split Hub Feature:

Not included

Web/spoke Relationship To Face Centerline:

Offset

Lightening Hole:

Not included

Integral Cooling Vane:

Not included

Groove Shape:

V

Bore Feature:

Included

Protruding Hub Characteristic:

Plain

Securing Location:

Aa end

Hub End Outside Diameter And Location:

5.500 inches aa end and 5.501 inches aa end

Distance From Outside Flange/rim To Hub End And Location:

1.560 inches aa end and 0.310 inches bb end

Special Features:

2nd counterbore 4.250 in.Dia, 0.406 in.Deep, located 1.530 in.From 2nd end

Surface Treatment:

Cadmium plated, qq-p-416, type 2, class 3

Style Designator:

Webbed or spoked

Surface Treatment:

Cadmium plated, qq-p-416, type 2, class 3

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

Yes - demil/mli

Fiig:

T353-a