

View Online at <https://aerobasegroup.com/nsn/3020-01-124-7963>

**Counterbore Diameter:**

Between 5.501 inches and 5.503 inches

**Counterbore Depth:**

0.310 inches

**Groove Depth:**

0.380 inches

**Groove Width:**

0.312 inches

**Outside Diameter:**

9.750 inches

**Overall Length:**

3.090 inches

**Bolt Circle Diameter:**

4.876 inches

**Thread Size:**

5/16-24

**Bore Length:**

3.090 inches

**V Groove Angle In Deg:**

40.0

**Securing Hole Quantity:**

6

**Taper Bore Major Diameter:**

1.500 inches

**Taper Bore Minor Diameter:**

1.369 inches

**Material And Location:**

Iron, ductile

**Face Width:**

1.530 inches

**Design Form:**

Webbed

**Bore Type:**

Tapered

**Bearings:**

Not included

**Groove Quantity:**

3

**Counterbore Feature:**

Included

**Counterbore Location:**

Bb end

**Hole Location:**

Thru pulley surface

**Keying Facility:**

Not included

**Securing Method:**

Threaded hole

**Split Hub Feature:**

Not included

**Web/spoke Relationship To Face Centerline:**

Offset

**Lightening Hole:**

Not included

**Integral Cooling Vane:**

Not included

**Groove Shape:**

V

**Bore Feature:**

Included

**Protruding Hub Characteristic:**

Plain

**Securing Location:**

Aa end

**Hub End Outside Diameter And Location:**

5.500 inches aa end and 5.501 inches aa end

**Distance From Outside Flange/rim To Hub End And Location:**

1.560 inches aa end and 0.310 inches bb end

**Special Features:**

2nd counterbore 4.250 in.Dia, 0.406 in.Deep, located 1.530 in.From 2nd end

**Surface Treatment:**

Cadmium plated, qq-p-416, type 2, class 3

**Style Designator:**

Webbed or spoked

**Surface Treatment:**

Cadmium plated, qq-p-416, type 2, class 3

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

Yes - demil/mli

**Fiig:**

T353-a