NSN 3020-01-128-9656

Spur Gear - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/3020-01-128-9656

| Body Style: |
|---|
| Plain, solid |
| Pitch Diameter: |
| 0.7187 inches |
| Teeth Quantity: |
| 23 |
| Hardness Rating: |
| 50.0 rockwell c body |
| Outside Diameter: |
| 0.781 inches |
| Tooth Form: |
| Standard |
| Pressure Angle: |
| 25.0000 degrees |
| Distance Between Body Face And Protruding Hub End: |
| 0.655 inches first end |
| Face Width: |
| 0.566 inches |
| Hub Style Designator: |
| 1 step both ends |
| End Length: |
| 0.183 inches second end |
| End Diameter: |
| 0.414 inches both ends |
| First Step Length: |
| 0.525 inches first end |
| First Step Diameter: |
| 0.479 inches first end |
| Material: |
| Steel comp 8620 |
| Material Specification: |
| Mil-s-8690 military specification single material response |
| Surface Treatment: |
| Tin body |
| Surface Treatment Specification: |
| Mil-t-1027, type 1 military specification single treatment response |
| Style Designator: |
| Protruding hubs |
| Shelf Life: |
| N/a |
| Unit Of Measure: |
| |

--

NSN 3020-01-128-9656

Spur Gear - Page 2 of 2



| _ | | •• | • • | | | | |
|----|----|----|-----|-----|-----|---|----|
| וו | em | ш | 112 | rız | 211 | n | ٠. |
| | | | | | | | |

No

Fiig:

A27300

Mil-std (military Standard):

Mil-s-8690 spec.