NSN 3020-01-129-7083

Sprocket Wheel - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/3020-01-129-7083

Outside Diameter:
6.575 inches
Outside Diameter:
7.000 inches
Bore Diameter:
Between 3.062 inches and 3.125 inches
Bore Length:
1.250 inches
End Application:
Fire pump model 3kb-4a 500 gpm 3500 rpm onboard 55 ft anb class coast guard vessels
Pitch Diameter:
6.685 inches
Taper Bore Major Diameter:
3.125 inches
Taper Bore Minor Diameter:
3.062 inches
Face Width:
3.625 inches
Guide:
Included
Design Form:
Webbed
Bore Type:
Tapered
Taper Major Diameter Location:
Aa end or bb end
Counterbore Feature:
Not included
Guide Type:
Sprocket side flange
Keying Facility:
Not included
Lightening Hole:
Not included
Belt/chain/film Size For Which Designed:
Positive drive belt
Teeth Row Quantity:
1
Teeth Quantity Per Row:
24
Hardness Rating Test Method:

Not rated

NSN 3020-01-129-7083 Sprocket Wheel - Page 2 of 2



Bore Bearing:
Not included
Tooth Pitch:
0.875 inches
Distance From Outside Flange/rim To Hub End And Location:
1.188 inches both ends
Material:
Iron, cast
Material:
Iron cast
Style Designator:
Webbed or spoked
Shelf Life:
N/a
Unit Of Measure:
Demilitarization:
No
Fiig:
T353-c