NSN 3020-01-134-3792

Groove Pulley - Page 1 of 3



View Online at https://aerobasegroup.com/nsn/3020-01-134-3792

Spline Major Diameter:
0.948 inches
Counterbore Diameter:
1.094 inches and 1.128 inches
Counterbore Depth:
0.406 inches and 0.220 inches
Groove Depth:
Between 0.815 inches and 0.949 inches
Groove Width:
0.438 inches
Outside Diameter:
7.560 inches
Overall Length:
4.894 inches
Spline Quantity:
14
Spline Minor Diameter:
Between 0.815 inches and 0.820 inches
End Application:
2350-00-078-4545 carrier, cargo, ft, m548
V Groove Angle In Deg:
36.0
Pitch Diameter:
6.090 inches
Material And Location:
Steel, astm a148
Face Width:
1.560 inches
Design Form:
Webbed
Bore Type:
Involute spline
Bearings:
Not included
Spline Pressure Angle In Deg:
30.0
Spline Length:
1.000 inches
Groove Quantity:
2
Counterbore Feature:

Included

NSN 3020-01-134-3792

Groove Pulley - Page 2 of 3



Salina Bitah Diameter
Spline Pitch Diameter: 0.8750 inches
Counterbore Location:
Both ends
Split Hub Feature:
Not included
Web/spoke Relationship To Face Centerline:
Not offset
Lightening Hole:
Not included
Integral Cooling Vane:
Not included
Groove Shape:
V
Bore Feature:
Included
Protruding Hub Characteristic:
Grooved
Securing Location:
Aa end
Hub End Outside Diameter And Location:
1.377 inches aa end and 1.378 inches aa end
Distance From Outside Flange/rim To Hub End And Location:
3.334 inches aa end
First End Groove Diameter And Location:
1.287 inches aa end and 1.295 inches aa end
First End Groove Width And Location:
0.056 inches aa end and 0.060 inches aa end
First End Length From Groove To End And Location:
0.109 inches aa end and 0.141 inches aa end
Special Features:
Static balanced to 0.500 in. Oz. By drilling/grinding
Surface Treatment:
Enamel
Style Designator:
Webbed or spoked
Surface Treatment:
Enameled
Shelf Life:
N/a
Unit Of Measure:
Demilitarization:

No

NSN 3020-01-134-3792

Groove Pulley - Page 3 of 3



Fiig:

T353-a