NSN 3020-01-142-1739

Spur Gear - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/3020-01-142-1739

Body Style:
Plain, solid
Attachment Method:
Clamp
Pitch Diameter:
4.6250 inches
Teeth Quantity:
74
Bore Style:
Plain both ends
Outside Diameter:
4.750 inches
Tooth Form:
Standard
Pressure Angle:
20.0000 degrees
Distance Between Body Face And Protruding Hub End:
0.500 inches first end
Face Width:
0.125 inches
Bore Diameter:
0.388 inches both ends
Hub Style Designator:
Split first end
Hub Diameter:
0.750 inches second end
Clamping Surface Length:
0.380 inches first end
Precision Classification:
Quality number 9
First Groove Width:
0.049 inches second end
First Groove Diameter:
0.701 inches second end
Distance From End To First Groove:
0.191 inches second end
Material:
Steel comp 4340
Material Specification:
Mil-s-5000 military specification single material response
Surface Treatment:
Phosphate manganese or phosphate zinc

NSN 3020-01-142-1739

Spur Gear - Page 2 of 2



Surface Treatment	Specification:
-------------------	----------------

Mil-p-16232, class 3 military specification all treatment responses

Style Designator:

Protruding hubs

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A27300

Mil-std (military Standard):

Mil-s-5000 spec.