## NSN 3020-01-142-1739

Spur Gear - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/3020-01-142-1739

**Body Style:** 

Plain, solid

**Attachment Method:** 

Clamp

**Pitch Diameter:** 

4.6250 inches

**Teeth Quantity:** 

74

Bore Style:

Plain both ends

Outside Diameter:

4.750 inches

Tooth Form:

Standard

Pressure Angle:

20.0000 degrees

Distance Between Body Face And Protruding Hub End:

0.500 inches first end

Face Width:

0.125 inches

Bore Diameter:

0.388 inches both ends

Hub Style Designator:

Split first end

Hub Diameter:

0.750 inches second end

**Clamping Surface Length:** 

0.380 inches first end

**Precision Classification:** 

Quality number 9

#### First Groove Width:

0.049 inches second end

First Groove Diameter:

0.701 inches second end

**Distance From End To First Groove:** 

0.191 inches second end

Material:

Steel comp 4340

Material Specification:

Mil-s-5000 military specification single material response

Surface Treatment:

Phosphate manganese or phosphate zinc

# NSN 3020-01-142-1739

Spur Gear - Page 2 of 2



### Surface Treatment Specification:

Mil-p-16232, class 3 military specification all treatment responses

### Style Designator:

Protruding hubs

Shelf Life:

N/a

## Unit Of Measure:

---

## Demilitarization:

No

Fiig:

A27300

## Mil-std (military Standard):

Mil-s-5000 spec.