NSN 3020-01-146-3163



Flat Pulley - Page 1 of 2 View Online at https://aerobasegroup.com/nsn/3020-01-146-3163 **Outside Diameter:** 8.750 inches **Overall Length:** 1.735 inches **Keyway Width:** 0.315 inches **Thread Size:** 3/8-16 **Bore Diameter:** 1.375 inches **Bore Length:** 1.640 inches **Distance From Center Of Bore To Bottom Of Keyway:** 0.836 inches **End Application:** Nsn 4210-01-486-1035 tfft (tactical fire fighting truck) **Securing Hole Quantity:** 6 **Material And Location:** Iron, cast Face Width: 1.070 inches **Design Form:** Webbed **Bore Type:** Straight Bearings: Not included **Counterbore Feature:** Not included **Hole Location:** Longitudinally through hub **Keying Facility:** Included **Keying Facility Type:** Keyway **Securing Method:** Threaded hole **Split Hub Feature:**

Not included Web/spoke Relationship To Face Centerline:

Not offset

NSN 3020-01-146-3163 Flat Pulley - Page 2 of 2



Lightening Hole:
Not included
Integral Cooling Vane:
Not included
Crown Face:
Not included
Rim Type:
Solid
Bore Feature:
Included
Protruding Hub Characteristic:
Stepped
Securing Location:
Aa end
Hub End Outside Diameter And Location:
3.749 inches aa end and 2.000 inches bb end
Distance From Outside Flange/rim To Hub End And Location:
0.665 inches aa end and 0.125 inches bb end
First Step Face Largest Diameter And Location:
4.880 inches aa end
First Step Length And Location:
0.410 inches aa end
Second Step Length And Location:
0.285 inches aa end
Hub End Outside Diameter And Location:
3.749 inches aa end
Distance From Outside Flange/rim To Hub End And Location:
0.695 inches aa end
Quantity:
1
Style Designator:
Webbed or spoked
Shelf Life:
N/a
Unit Of Measure:
-
Demilitarization:
No
Fiig:
T353-a