NSN 3020-01-148-2949

Cone Pulley - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/3020-01-148-2949

Groove Depth:
10.4 millimeters and 10.4 millimeters and 10.4 millimeters
Groove Width:
9.6 millimeters and 9.6 millimeters and 9.6 millimeters
Overall Length:
69.6 millimeters
Bolt Circle Diameter:
53.9 millimeters
Bore Diameter:
19.0 millimeters
Bore Length:
3.2 millimeters
Drilled Hole Diameter:
11.8 millimeters
V Groove Angle In Deg:
36.0 and 36.0 and 36.0
Securing Hole Quantity:
4
Face Type:
Step groove
Material And Location:
Steel, sae 1008
Face Width:
15.2 millimeters and 36.0 millimeters
Design Form:
Webbed
Bore Type:
Straight
Groove Quantity:
3
Counterbore Feature:
Not included
Step Outside Diameter:
158.2 millimeters and 139.2 millimeters
Hole Location:
Thru pulley body
Keying Facility:
Not included
Securing Method:
Drilled hole
Web/spoke Relationship To Face Centerline:
Not offset

NSN 3020-01-148-2949Cone Pulley - Page 2 of 2



Lightening Hole:
Not included
Integral Cooling Vane:
Not included
Groove Shape:
V
Standard V-belt Section Designation For Which Designed:
Any acceptable and any acceptable and any acceptable
Securing Location:
Aa end
Bore Bearing:
Not included
Distance From Outside Flange/rim To Hub End And Location:
18.5 millimeters aa end and 66.4 millimeters bb end
V Groove Pitch Diameter:
152.4 millimeters and 152.4 millimeters and 133.4 millimeters
Surface Treatment:
Phosphate
Style Designator:
Webbed or spoked
Surface Treatment:
Phosphate
Shelf Life:
N/a
Unit Of Measure:
Demilitarization:
No
Fiig:
T353-b