NSN 3020-01-148-2950

Cone Pulley - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/3020-01-148-2950

Groove Depth:

10.4 millimeters and 10.4 millimeters and 14.0 millimeters

Groove Width:

9.6 millimeters and 9.6 millimeters and 12.7 millimeters

Overall Length:

69.7 millimeters

Bolt Circle Diameter:

53.9 millimeters

Bore Diameter:

19.0 millimeters

Bore Length:

3.2 millimeters

Drilled Hole Diameter:

11.8 millimeters

V Groove Angle In Deg:

36.0 and 36.0 and 36.0

Securing Hole Quantity:

4

Face Type:

Step groove

Material And Location:

Steel, sae 1008

Face Width:

21.0 millimeters and 30.9 millimeters

Design Form:

Webbed

Bore Type:

Straight

Groove Quantity:

3

Counterbore Feature:

Not included

Step Outside Diameter:

159.2 millimeters and 139.2 millimeters

Hole Location:

Thru pulley surface

Keying Facility:

Not included

Securing Method:

Drilled hole

Web/spoke Relationship To Face Centerline:

Not offset

NSN 3020-01-148-2950

Cone Pulley - Page 2 of 2

Lightening Hole: Not included Integral Cooling Vane: Not included Groove Shape: V Standard V-belt Section Designation For Which Designed: Any acceptable and any acceptable and any acceptable Securing Location: Aa end **Bore Bearing:** Not included Distance From Outside Flange/rim To Hub End And Location: 16.0 millimeters aa end and 66.5 millimeters bb end V Groove Pitch Diameter: 133.4 millimeters and 133.4 millimeters and 151.8 millimeters Surface Treatment: Phosphate Style Designator: Webbed or spoked **Surface Treatment:** Phosphate Shelf Life: N/a Unit Of Measure: ---**Demilitarization:** No Fiig: T353-b

