NSN 3020-01-148-6983

Cone Pulley - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/3020-01-148-6983

Groove Depth:
14.0 millimeters and 14.0 millimeters and 14.0 millimeters and 14.0 millimeters
Groove Width:
12.7 millimeters and 12.7 millimeters and 9.6 millimeters and 9.6 millimeters
Overall Length:
84.6 millimeters
Bore Diameter:
56.0 millimeters
Bore Length:
84.6 millimeters
End Application:
2320-01-123-6827 truck, cargo
Drilled Hole Diameter:
10.8 millimeters
V Groove Angle In Deg:
36.0 and 36.0 and 36.0 and 36.0
Securing Hole Quantity:
4
Face Type:
Step groove
Material And Location:
Steel, sae 1008
Face Width:
18.0 millimeters and 18.0 millimeters and 18.0 millimeters and 18.0 millimeters
Design Form:
Plain
Bore Type:
Straight
Groove Quantity:
4
Counterbore Feature:
Not included
Step Outside Diameter:
120.7 millimeters and 60.0 millimeters
Hole Location:
Equally spaced on hub
Keying Facility:
Not included
Securing Method:
Drilled hole
Split Hub Feature:

Not included

NSN 3020-01-148-6983 Cone Pulley - Page 2 of 2



Lightening Hole:
Not included
Integral Cooling Vane:
Not included
Groove Shape:
V
Standard V-belt Section Designation For Which Designed:
Any acceptable and any acceptable and any acceptable and any acceptable
Protruding Hub Characteristic:
Plain
Securing Location:
Aa end
Bore Bearing:
Not included
Hub End Outside Diameter And Location:
120.7 millimeters aa end
Distance From Outside Flange/rim To Hub End And Location:
120.0 millimeters aa end
V Groove Pitch Diameter:
168.7 millimeters and 168.7 millimeters and 168.7 millimeters and 168.7 millimeters
Surface Treatment:
Phosphate
Style Designator:
Plain
Surface Treatment:
Phosphate
Shelf Life:
N/a
Unit Of Measure:

Demilitarization:
No
Fiig:
T353-b