NSN 3020-01-148-8318

Spur Gear-slip Clutch - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/3020-01-148-8318 **Attachment Method:** Mounting hole Pitch Diameter: 3.4375 inches **Torque Capacity:** 32.00 inch-ounces preset **Teeth Quantity:** 165 **Bore Style:** Plain both ends **Mounting Hole Thread Series Designator:** Unc transversely through hub, first end **Mounting Hole Thread Size:** 0.138 inches transversely through hub, first end **Mounting Hole Type And Quantity:** 1 threaded transversely through hub, first end **Outside Diameter:** 3.4792 inches Nominallength: 0.800 inches **Tooth Form:** Standard **Pressure Angle:** 14.5000 degrees **Distance Between Body Face And Protruding Hub End:** 0.323 inches both ends **Face Width:** 0.125 inches **Bore Diameter:** 0.250 inches both ends Distance Between Face Edge And Body End: 0.352 inches **Hub Style Designator:** Plain first end **Hub Diameter:** 0.625 inches first end Material: Steel comp 303 **Material Specification:** Mil-s-7720 military specification single material response

Surface Treatment:

Passivate

NSN 3020-01-148-8318

Spur Gear-slip Clutch - Page 2 of 2



Style Designator:
Fixed torque, spring washer loaded
Shelf Life:
N/a
Unit Of Measure:
Demilitarization:
No
Fiig:

Mil-std (military Standard):

Mil-s-7720 spec.

A27300