
## NSN 3020-01-148-8318

Spur Gear-slip Clutch - Page 1 of 2





## **Attachment Method:** Mounting hole **Pitch Diameter:** 3.4375 inches **Torque Capacity:** 32.00 inch-ounces preset **Teeth Quantity:** 165 Bore Style: Plain both ends Mounting Hole Thread Series Designator: Unc transversely through hub, first end **Mounting Hole Thread Size:** 0.138 inches transversely through hub, first end Mounting Hole Type And Quantity: 1 threaded transversely through hub, first end **Outside Diameter:** 3.4792 inches Nominallength: 0.800 inches **Tooth Form:** Standard Pressure Angle: 14.5000 degrees **Distance Between Body Face And Protruding Hub End:** 0.323 inches both ends Face Width: 0.125 inches **Bore Diameter:** 0.250 inches both ends Distance Between Face Edge And Body End: 0.352 inches Hub Style Designator: Plain first end **Hub Diameter:** 0.625 inches first end Material: Steel comp 303 **Material Specification:** Mil-s-7720 military specification single material response Surface Treatment: Passivate

## NSN 3020-01-148-8318

Spur Gear-slip Clutch - Page 2 of 2

Style Designator:

Fixed torque, spring washer loaded

Shelf Life:

N/a

Unit Of Measure:

---

Demilitarization:

No

Fiig:

A27300

Mil-std (military Standard):

Mil-s-7720 spec.

