

View Online at <https://aerobasegroup.com/nsn/3020-01-149-5915>

**Counterbore Diameter:**

34.0 millimeters

**Counterbore Depth:**

3.0 millimeters

**Outside Diameter:**

153.1 millimeters

**Keyway Width:**

4.8 millimeters

**Bore Diameter:**

32.5 millimeters

**Bore Length:**

18.3 millimeters

**Distance From Center Of Bore To Bottom Of Keyway:**

19.2 millimeters

**Pitch Diameter:**

145.7 millimeters

**Face Width:**

18.3 millimeters

**Guide:**

Not included

**Design Form:**

Webbed

**Bore Type:**

Straight

**Metallic Hardness Rating And Location:**

241.0 brinell standard body and 302.0 brinell standard body

**Counterbore Feature:**

Included

**Counterbore Location:**

Aa end

**Keying Facility:**

Included

**Keying Facility Type:**

Keyway

**Securing Method:**

Slotted

**Lightening Hole:**

Not included

**Protruding Hub Characteristic:**

Plain

**Securing Location:**

Aa end

**Belt/chain/film Size For Which Designed:**

Silent chain

**Teeth Row Quantity:**

2

**Center To Center Distance Between Teeth Rows:**

7.3 millimeters

**Teeth Quantity Per Row:**

36

**Hardness Rating Test Method:**

Rockwell

**Teeth Hardness Rating:**

45.0 rockwell c

**Bore Bearing:**

Not included

**Hub External Keyway:**

Not included

**Tooth Pitch:**

12.7 millimeters

**Hub End Outside Diameter And Location:**

55.0 millimeters aa end

**Distance From Outside Flange/rim To Hub End And Location:**

3.0 millimeters aa end

**Material:**

Iron, ductile, sae grade d7003

**Material:**

Iron, ductile, sae grade d7003

**Quantity:**

1

**Style Designator:**

Webbed or spoked

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fiig:**

T353-c