

View Online at <https://aerobasegroup.com/nsn/3020-01-149-5915>

Counterbore Diameter:

34.0 millimeters

Counterbore Depth:

3.0 millimeters

Outside Diameter:

153.1 millimeters

Keyway Width:

4.8 millimeters

Bore Diameter:

32.5 millimeters

Bore Length:

18.3 millimeters

Distance From Center Of Bore To Bottom Of Keyway:

19.2 millimeters

Pitch Diameter:

145.7 millimeters

Face Width:

18.3 millimeters

Guide:

Not included

Design Form:

Webbed

Bore Type:

Straight

Metallic Hardness Rating And Location:

241.0 brinell standard body and 302.0 brinell standard body

Counterbore Feature:

Included

Counterbore Location:

Aa end

Keying Facility:

Included

Keying Facility Type:

Keyway

Securing Method:

Slotted

Lightening Hole:

Not included

Protruding Hub Characteristic:

Plain

Securing Location:

Aa end

Belt/chain/film Size For Which Designed:

Silent chain

Teeth Row Quantity:

2

Center To Center Distance Between Teeth Rows:

7.3 millimeters

Teeth Quantity Per Row:

36

Hardness Rating Test Method:

Rockwell

Teeth Hardness Rating:

45.0 rockwell c

Bore Bearing:

Not included

Hub External Keyway:

Not included

Tooth Pitch:

12.7 millimeters

Hub End Outside Diameter And Location:

55.0 millimeters aa end

Distance From Outside Flange/rim To Hub End And Location:

3.0 millimeters aa end

Material:

Iron, ductile, sae grade d7003

Material:

Iron, ductile, sae grade d7003

Quantity:

1

Style Designator:

Webbed or spoked

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

T353-c