

View Online at <https://aerobasegroup.com/nsn/3020-01-150-0464>

**Outside Diameter:**

4.687 inches

**Outside Diameter:**

4.687 inches

**Bore Diameter:**

0.500 inches

**Bore Length:**

1.810 inches

**End Application:**

Fire pump

**Pitch Diameter:**

4.456 inches

**Face Width:**

3.380 inches

**Guide:**

Included

**Design Form:**

Plain

**Bore Type:**

Straight

**Counterbore Feature:**

Not included

**Guide Type:**

Sprocket side flange

**Keying Facility:**

Not included

**Lightening Hole:**

Not included

**Protruding Hub Characteristic:**

Plain

**Belt/chain/film Size For Which Designed:**

Positive drive belt

**Teeth Row Quantity:**

1

**Teeth Quantity Per Row:**

28

**Hardness Rating Test Method:**

Not rated

**Bore Bearing:**

Not included

**Hub External Keyway:**

Not included

**Tooth Pitch:**

0.500 inches

**Distance From Outside Flange/rim To Hub End And Location:**

0.630 inches both ends

**Special Features:**

Bushing must be bored to suit pump shaft upon receipt

**Material:**

Iron, cast, qq-i-652, class 30

**Material:**

Iron cast uns f12101

**Material Specification:**

Qq-i-652, class 30 federal specification single material response

**Style Designator:**

Webbed or spoked

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fig:**

T353-c