# NSN 3020-01-151-2645

Spur Gear - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/3020-01-151-2645

Plain, solid

**Spline Quantity:** 

30 both ends

# Attachment Method:

Mounting hole

# **Pitch Diameter:**

3.2500 inches

## **Teeth Quantity:**

30

#### Bore Style:

Involute spline both ends

#### Spline Pitch Diameter:

1.8750 inches both ends

#### **Features Provided:**

Casehardened

# Mounting Hole Type And Quantity:

2 plain transversely through hub, first end

#### **Outside Diameter:**

3.500 inches

### Tooth Form:

Standard

#### Pressure Angle:

20.0000 degrees

#### Distance Between Body Face And Protruding Hub End:

2.109 inches first end

#### Face Width:

2.109 inches

#### Bore Diameter:

1.938 inches both ends

#### Hub Style Designator:

1 step first end

#### End Length:

2.813 inches first end

#### End Diameter:

2.750 inches first end

#### First Step Length:

0.344 inches first end

#### First Step Diameter:

1.766 inches first end

### Mounting Hole Diameter:

0.188 inches transversely through hub, first end

# NSN 3020-01-151-2645

Spur Gear - Page 2 of 2



#### **Special Features:**

Mtg holes angular drilled; ctrbore 1st end 2.078 in. Diameter by 1.078 in. Depth, ctrbore 2nd end 2.140 in. Diameter by 0.500 in. Depth

Material:

Steel

Style Designator:

Protruding hub

Shelf Life:

N/a

Unit Of Measure:

---

Demilitarization:

No

Fiig:

A27300