NSN 3020-01-160-6516

Spur Gear - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/3020-01-160-6516

| Body Style: |
|---|
| Webbed, solid |
| Pitch Diameter: |
| 3.8333 inches |
| Teeth Quantity: |
| 46 |
| Bore Style: |
| Plain both ends |
| Outside Diameter: |
| 3.934 inches |
| Tooth Form: |
| Standard |
| Pressure Angle: |
| 20.0000 degrees |
| Distance Between Body Face And Protruding Hub End: |
| 4.020 inches first end |
| Body Recess Depth: |
| 0.806 inches second end |
| Face Width: |
| 1.030 inches |
| Bore Diameter: |
| 1.500 inches both ends |
| Hub Style Designator: |
| 1 step first end |
| End Length: |
| 3.490 inches first end |
| End Diameter: |
| 1.938 inches first end |
| First Step Length: |
| 0.530 inches first end |
| First Step Diameter: |
| 2.760 inches first end |
| Special Features: |
| Partially involute splined bore |
| Material: |
| Steel comp 4027 or steel comp 4047h |
| Material Specification: |
| 66aisi/sae4027 federal standard 1st material response or 66aisi/sae4047h federal standard 2nd material response |
| Style Designator: |
| Protruding hub, recessed body |
| Furnished Items And Quantity: |

1 plug

NSN 3020-01-160-6516

Spur Gear - Page 2 of 2



| C | ha | Ιf | 1 | ife | |
|---|-----|----|---|-------|--|
| • | ııe | | _ | .II C | |

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A27300