
NSN 3020-01-161-7709

Bevel Gear - Page 1 of 2





Body Style:

Plain, solid

Attachment Method:

Mounting hole

Pitch Diameter:

92.0 millimeters

Teeth Quantity:

23

Bore Style:

10b w/ 2 keyways both ends

Hardness Rating:

59.0 rockwell c and 62.0 rockwell c

Mounting Hole Type And Quantity:

2 plain axially through body, first end

Outside Diameter:

97.6 millimeters

Nominallength:

49.3 millimeters

Teeth Type:

Straight

Pressure Angle:

20.0000 degrees

Pitch Angle:

45.0000 degrees

Distance Between Body Face And Protruding Hub End:

31.8 millimeters first end

Body Recess Depth:

3.3 millimeters second end

Face Width:

28.0 millimeters

Bore Diameter:

26.0 millimeters both ends

Keyway Width:

8.0 millimeters both ends

Distance From Bore Center To Keyway Bottom:

15.1 millimeters both ends

Hub Style Designator:

Plain first end

Hub Diameter:

45.0 millimeters first end

Mounting Hole Diameter:

6.5 millimeters axially through body, first end

NSN 3020-01-161-7709

Bevel Gear - Page 2 of 2



Bolt Hole Circle Diameter:

38.0 millimeters axially through body, first end

Special Features:

Mtg holes at 75 degrees angle to tooth center line, not totally parallel to bore

Material:

Steel comp 8620

Material Specification:

Sae 8620 opt. 5117h assn standard single material response

Style Designator:

Side face, back hub protruding

Shelf Life:

N/a

Unit Of Measure:

Demilitarization:

No

Fiig:

A27300