NSN 3020-01-165-1539

Spur Gear - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/3020-01-165-1539 **Body Style:** Plain, solid **Attachment Method:** Mounting hole Pitch Diameter: 1.5000 inches **Teeth Quantity:** 12 **Bore Style:** 10a w/ keyway both ends **Mounting Hole Thread Series Designator:** Unf transversely through hub, first end Mounting Hole Thready Qty Per Inch (tpi): 28 transversely through hub, first end **Hardness Rating:** 48.0 rockwell c and 52.0 rockwell c **Mounting Hole Thread Size:** 0.250 inches transversely through hub, first end **Mounting Hole Type And Quantity:** 1 threaded transversely through hub, first end **Outside Diameter:** 1.750 inches **Tooth Form:** Standard **Pressure Angle:** 14.5000 degrees **Distance Between Body Face And Protruding Hub End:** 0.750 inches first end **Face Width:** 1.250 inches **Bore Diameter:** 0.189 inches both ends **Keyway Width:** 0.189 inches both ends **Distance From Bore Center To Keyway Bottom:** 0.466 inches both ends **Hub Style Designator:**

Plain first end

Hub Diameter:

1.120 inches first end

Material:

Steel comp 4140

NSN 3020-01-165-1539

Spur Gear - Page 2 of 2



Material Specification:
Mil-s-5626, comp 4140 military specification single material response

Protruding hub

Style Designator:

Shelf Life:

N/a

Unit Of Measure:

Demilitarization:

No

Fiig:

A27300

Mil-std (military Standard):

Mil-s-5626 spec.