## NSN 3020-01-166-4194



Spur Gear - Page 1 of 2 View Online at https://aerobasegroup.com/nsn/3020-01-166-4194 **Body Style:** Plain, solid Pitch Diameter: 0.8750 inches **Teeth Quantity:** 28 **Bore Style:** Plain both ends **Backlash Designation:** Grade c Hardness Rating: 65.0 rockwell c teeth and 68.0 rockwell c teeth **Outside Diameter:** 0.938 inches **Tooth Form:** Standard **Pressure Angle:** 20.0000 degrees **Distance Between Body Face And Protruding Hub End:** 0.250 inches first end Face Width: 0.312 inches **Bore Diameter:** 0.375 inches both ends **Hub Style Designator:** Pinned first end **Hub Diameter:** 0.620 inches first end **Precision Classification:** Quality number 10 Material: Steel comp 630 **Material Specification:** Ams5643 assn standard single material response

Ams5643 assn standard single material response

Surface Treatment:

Passivate

Surface Treatment Specification:

Mil-f-14072, finish e300 military specification single treatment response

Style Designator:

Protruding hub

Shelf Life:

N/a

## NSN 3020-01-166-4194

Spur Gear - Page 2 of 2



U	n	it	Of	Μe	eas	ur	e:

--

Demilitarization:

No

Fiig:

A27300

Mil-std (military Standard):

Mil-f-14072 spec.