## NSN 3020-01-166-6403

Cone Pulley - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/3020-01-166-6403 **Groove Depth:** 0.735 inches **Groove Width:** 0.438 inches **Overall Length: 7.562** inches **Keyway Width:** Between 0.251 inches and 0.253 inches **Bore Diameter:** Between 1.000 inches and 1.002 inches **Bore Length:** 1.875 inches **Distance From Center Of Bore To Bottom Of Keyway:** Between 0.609 inches and 0.613 inches V Groove Angle In Deg: 35.0 and 36.0 Face Type: Step groove **Material And Location:** Steel, astm a27, grade 65-35 Face Width: 7.562 inches **Design Form:** Webbed **Bore Type:** Straight **Groove Quantity: Counterbore Feature:** Not included **Step Outside Diameter:** Between 4.519 inches and 4.569 inches **Keying Facility:** Included **Keying Facility Type:** Keyway Web/spoke Relationship To Face Centerline: Not offset **Lightening Hole:** Not included **Integral Cooling Vane:** 

Not included

## **NSN 3020-01-166-6403** Cone Pulley - Page 2 of 2



| Groove Shape:   |
|---|
| V   |
| Bore Bearing:   |
| Not included  |
| Hub End Outside Diameter And Location:                    |
| 4.569 inches aa end and 1.620 inches bb end               |
| Distance From Outside Flange/rim To Hub End And Location: |
| 1.840 inches aa end and 0.832 inches bb end               |
| Quantity:   |
| 1   |
| Style Designator:   |
| Webbed or spoked  |
| Shelf Life:   |
| N/a   |
| Unit Of Measure:  |
|   |
| Demilitarization:   |
| No  |
| Fiig:   |
| T353-b  |
|   |