
Cone Pulley - Page 1 of 2



Spline Major Diameter:

2.169 inches

Counterbore Diameter:

2.600 inches

Counterbore Depth:

0.380 inches

Overall Length:

2.560 inches

Spline Quantity:

16

Spline Minor Diameter:

1.881 inches

Large End Outside Diameter:

10.250 inches

Small End Outside Diameter:

8.609 inches

Face Type:

Tapered cone

Material And Location:

Steel, mil-s-6758

Face Width:

0.750 inches

Design Form:

Plain

Bore Type:

Involute spline

Spline Pressure Angle In Deg:

30.0

Spline Length:

0.370 inches

Counterbore Feature:

Included

Spline Pitch Diameter:

2.000 inches

Counterbore Location:

Bb end

Split Hub Feature:

Not included

Lightening Hole:

Included

Integral Cooling Vane:

Not included



NSN 3020-01-170-9292

Cone Pulley - Page 2 of 2



Protruding Hub Characteristic: Grooved Groove/step Location: Aa end **Bore Bearing:** Not included Hub End Outside Diameter And Location: 2.750 inches aa end and 3.300 inches bb end Distance From Outside Flange/rim To Hub End And Location: 1.810 inches aa end and 0.380 inches bb end First End Groove Diameter And Location: 2.380 inches aa end First End Groove Width And Location: 0.320 inches aa end First End Length From Groove To End And Location: 0.240 inches aa end Hub End Outside Diameter And Location: 2.750 inches aa end Distance From Outside Flange/rim To Hub End And Location: 1.810 inches aa end **Special Features:** 24 holes 0.812 diameter bevel face Surface Treatment: Enamel **Style Designator:** Plain Surface Treatment: Enameled Shelf Life: N/a Unit Of Measure: ---**Demilitarization:** No Fiig: T353-b