

View Online at <https://aerobasegroup.com/nsn/3020-01-171-3383>

Groove Depth:

0.141 inches

Groove Width:

0.750 inches

Outside Diameter:

19.219 inches

Overall Length:

2.250 inches

Bolt Circle Diameter:

6.375 inches and 15.680 inches

Keyway Width:

0.502 inches

Bore Diameter:

3.937 inches

Bore Length:

2.250 inches

Distance From Center Of Bore To Bottom Of Keyway:

2.201 inches

Drilled Hole Diameter:

0.343 inches and 0.750 inches

Groove Radius:

0.312 inches

Securing Hole Quantity:

6 and 12

Material And Location:

Steel, aisi 4150

Face Width:

0.812 inches

Design Form:

Plain

Bore Type:

Straight

Bearings:

Not included

Groove Quantity:

1

Counterbore Feature:

Not included

Hole Location:

6 holes equally spaced on pulley surface; 12 holes equally spaced on pulley surface

Keying Facility:

Included

Keying Facility Type:

Keyway

Securing Method:

Drilled hole

Split Hub Feature:

Not included

Lightening Hole:

Not included

Integral Cooling Vane:

Not included

Groove Shape:

U

Bore Feature:

Included

Protruding Hub Characteristic:

Stepped

Securing Location:

Pulley surface

Hub End Outside Diameter And Location:

4.998 inches both ends

Distance From Outside Flange/rim To Hub End And Location:

0.724 inches both ends

First Step Face Largest Diameter And Location:

7.250 inches both ends

First Step Length And Location:

0.390 inches both ends

Second Step Length And Location:

0.234 inches both ends

Hub End Outside Diameter And Location:

4.998 inches both ends

Distance From Outside Flange/rim To Hub End And Location:

0.719 inches both ends

Quantity:

1

Style Designator:

Plain

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

T353-a