## NSN 3020-01-178-0742



Spur Gear - Page 1 of 2

View Online at https://aerobasegroup.com/nsn/3020-01-178-0742

Body Style:
Plain, solid
Pitch Diameter:
0.2500 inches
Teeth Quantity:
8
Bore Style:
Plain both ends
Backlash Designation:
Grade c
Outside Diameter:
0.311 inches

Pressure Angle: 20.0000 degrees

**Distance Between Body Face And Protruding Hub End:** 

0.062 inches first end

**Face Width:** 

Tooth Form: Standard

0.100 inches

**Bore Diameter:** 

0.095 inches both ends

**Hub Style Designator:** 

Plain both ends

**Hub Diameter:** 

0.148 inches both ends

**Precision Classification:** 

Quality number 10

Special Features:

0.62 inch deep, .035 inch wide cutout on teeth four places

Material:

Steel comp 303

**Material Specification:** 

Qq-s-763, class 303, cond a federal specification single material response

**Surface Treatment:** 

**Passivate** 

**Surface Treatment Specification:** 

Mil-f-14072, finish e300 military specification single treatment response

**Style Designator:** 

Protruding hubs

Shelf Life:

N/a

## NSN 3020-01-178-0742

Spur Gear - Page 2 of 2



		• -						
	In		Of	RЛ	മാ	CI	ır	Δ.
L	,,,			IVI	ca			

--

Demilitarization:

No

Fiig:

A27300

Mil-std (military Standard):

Mil-f-14072 spec.