## NSN 3020-01-183-1600

Spur Gear Sector - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/3020-01-183-1600

Attachment Method:				
Mounting hole				
Teeth Quantity:				
4				
Bore Style:				
W/counterbore both ends				
Pitch Radius:				
1.1000 inches				
Mounting Hole Type And Quantity:				
6 counterbored axially through flange				
Pressure Angle:				
20.0000 degrees				
Distance Between Body Face And Protruding Hub End:				
1.250 inches first end				
Face Width:				
0.625 inches				
Bore Diameter:				
1.468 inches counterbore, first end				
Counterbore Depth:				
0.047 inches counterbore, first end				
Counterbore Diameter:				
1.750 inches counterbore, first end				
Hub Style Designator:				
2 steps first end				
Outside Radius:				
1.200 inches				
End Length:				
0.188 inches first end				
End Diameter:				
1.850 inches first end				
First Step Length:				
0.375 inches first end				
First Step Diameter:				
4.224 inches first end				
Arc Length:				
1.257 inches				
Second Step Length:				

Mounting Hole Diameter:

0.687 inches first endSecond Step Diameter:1.875 inches first end

0.281 inches axially through flange

## NSN 3020-01-183-1600

Spur Gear Sector - Page 2 of 2



Bolt	Hole	Circle	Diameter:
	7 : 1-		

2.937 inches axially through flange

**Special Features:** 

Hub 1st step is a mtg flange

Material:

Steel comp 1144

**Material Specification:** 

Aisi 1144 assn standard single material response

Style Designator:

Protruding hub

Shelf Life:

N/a

**Unit Of Measure:** 

Demilitarization:

No

Fiig:

A27300