## NSN 3020-01-189-8870

Spur Gear - Page 1 of 2

**Body Style:** 



View Online at https://aerobasegroup.com/nsn/3020-01-189-8870

Plain, solid
Attachment Method:
Mounting hole
Pitch Diameter:
1.7500 inches
Teeth Quantity:
42
Bore Style:
10a w/ keyway both ends
Mounting Hole Thread Series Designator:
Unc transversely through hub, second end
Mounting Hole Thread Size:
0.112 inches transversely through hub, second end
Mounting Hole Type And Quantity:
1 threaded transversely through hub, second end
Outside Diameter:
1.832 inches
Pressure Angle:
20.0000 degrees
Distance Between Body Face And Protruding Hub End:
0.290 inches second end
Body Recess Depth:
0.137 inches first end
Face Width:
0.250 inches
Bore Diameter:
0.375 inches both ends
Keyway Width:
0.125 inches both ends
Distance From Bore Center To Keyway Bottom:
0.231 inches both ends
Hub Style Designator:
1 step second end
End Length:
0.070 inches second end
End Diameter:
0.625 inches second end
First Step Length:
0.220 inches second end
First Step Diameter:
0.875 inches second end

## NSN 3020-01-189-8870

Spur Gear - Page 2 of 2



Special Features:
Mounting hole located first step second end hub
Material:
Steel
Material Specification:
Mil-s-6709 military specification single material response
Surface Treatment:
Phosphate manganese
Surface Treatment Specification:
Mil-p-16232 type m class 1 military specification single treatment response
Style Designator:
Protruding hub, recessed body
Shelf Life:
N/a
Unit Of Measure:
Demilitarization:
Yes - demil/mli
Fiig:

Mil-std (military Standard): Mil-s-6709 spec.

A27300