NSN 3020-01-189-9475

Spur Gear - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/3020-01-189-9475 **Body Style:** Plain, solid **Spline Quantity:** 31 both ends **End Application:** F16 acft Pitch Diameter: 0.6562 inches **Teeth Quantity:** 21 **Bore Style:** Involute spline both ends **Spline Pitch Diameter:** 0.6458 inches both ends **Hardness Rating:** 58.0 rockwell c **Outside Diameter:** 0.718 inches Nominallength: 0.880 inches **Tooth Form:** Standard Pressure Angle: 20.0000 degrees **Distance Between Body Face And Protruding Hub End:** 0.615 inches first end **Face Width:** 0.265 inches **Bore Diameter:** 0.654 inches both ends **Counterbore Depth:** 0.445 inches both ends **Counterbore Diameter:** 0.405 inches both ends **Hub Style Designator:** 1 groove first end **Hub Diameter:** 0.812 inches first end **Precision Classification:**

Quality number 7 **First Groove Width:** 0.090 inches first end

NSN 3020-01-189-9475 Spur Gear - Page 2 of 2



First Groove Diameter:	
0.570 inches first end	
Distance From End To First Groove:	
0.425 inches first end	
Material:	
Steel comp e9310	
Material Specification:	
Ams 6260 assn standard single material response	
Surface Treatment:	
Oxide	
Surface Treatment Specification:	
Mil-c-13924, class 2 military specification single treatment response	
Style Designator:	
Protruding hub	
Shelf Life:	
N/a	
Unit Of Measure:	
-	
Demilitarization:	
Yes - demil/mli	
Fiig:	
A27300	
Mil-std (military Standard):	
Mil-c-13924 spec.	