NSN 3020-01-189-9476

Spur Gear - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/3020-01-189-9476

Body Style:
Plain, solid
Spline Quantity:
11 both ends
End Application:
F16 acft
Pitch Diameter:
0.9687 inches
Teeth Quantity:
31
Bore Style:
Involute spline both ends
Spline Pitch Diameter:
0.2290 inches both ends
Hardness Rating:
58.0 rockwell c
Outside Diameter:
1.031 inches
Nominallength:
0.820 inches
Tooth Form:
Standard
Pressure Angle:
20.0000 degrees
Distance Between Body Face And Protruding Hub End:
0.310 inches both ends
Face Width:
0.200 inches
Bore Diameter:
0.240 inches both ends
Counterbore Depth:
0.190 inches both ends
Counterbore Diameter:
0.285 inches both ends
End Length:
0.250 inches both ends
Precision Classification:
Quality number 7
End Diameter:
0.375 inches both ends
First Step Length:

0.030 inches both ends

NSN 3020-01-189-9476

Spur Gear - Page 2 of 2



First Step Diameter:
0.440 inches both ends
Material:
Steel comp e9310
Material Specification:
Ams 6260 assn standard single material response
Surface Treatment:
Oxide
Surface Treatment Specification:
Mil-c-13924, class 2 military specification single treatment response
Style Designator:
Protruding hubs
Shelf Life:
N/a
Unit Of Measure:
Demilitarization:
Yes - demil/mli
Fiig:
A27300
Mil-std (military Standard):
Mil-c-13924 spec.