## NSN 3020-01-189-9477

Spur Gear - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/3020-01-189-9477 **Body Style:** Plain, solid **Spline Quantity:** 27 both ends **End Application:** F16 acft Pitch Diameter: 2.1875 inches **Teeth Quantity:** 70 **Bore Style:** Involute spline both ends **Spline Pitch Diameter:** 0.8440 inches both ends **Outside Diameter:** 2.250 inches Nominallength: 0.820 inches **Tooth Form:** Standard Pressure Angle: 20.0000 degrees **Distance Between Body Face And Protruding Hub End:** 0.670 inches first end Face Width: 0.125 inches **Bore Diameter:** 0.856 inches both ends **Counterbore Depth:** 0.190 inches second end **Counterbore Diameter:** 0.940 inches second end **Hub Style Designator:** Plain first end **Hub Diameter:** 1.375 inches first end Material: Steel comp e9310 **Material Specification:** 

Ams 6260 assn standard single material response **Surface Treatment:** 

Oxide

## NSN 3020-01-189-9477

Spur Gear - Page 2 of 2



Surface	Treatment	Specification:
Juliace	HEAUHEIL	opecilication.

Mil-c-13924, class 2 military specification single treatment response

**Style Designator:** 

Protruding hub

Shelf Life:

N/a

**Unit Of Measure:** 

--

Demilitarization:

Yes - demil/mli

Fiig:

A27300

Mil-std (military Standard):

Mil-c-13924 spec.