## NSN 3020-01-193-7342

Spur Antibacklash Gear - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/3020-01-193-7342 **Attachment Method:** Clamp Pitch Diameter: 0.7812 inches **Teeth Quantity:** 50 **Bore Style:** Plain both ends **Outside Diameter:** 0.8125 inches **Tooth Form:** Standard **Pressure Angle:** 20.0000 degrees **Distance Between Body Face And Protruding Hub End:** 0.281 inches first end **Face Width:** 0.104 inches **Bore Diameter:** 0.125 inches both ends **Hub Style Designator:** Split first end **Hub Diameter:** 0.187 inches first end **Clamping Surface Length:** 0.250 inches first end Material: Aluminum alloy 2024 body **Material Specification:** Qq-a-225/6, t4 federal specification single material response body **Surface Treatment:** Passivate hub **Surface Treatment Specification:** Qq-p-35, type 2 federal specification single treatment response hub **Style Designator:** Protruding hub Shelf Life: N/a **Unit Of Measure:** 

Demilitarization:

No

## NSN 3020-01-193-7342

Spur Antibacklash Gear - Page 2 of 2



Fiig:

A27300

Mil-std (military Standard):

Mil-a-8625 spec.