NSN 3020-01-204-5879

Sprocket Wheel - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/3020-01-204-5879 **Overall Length:** 0.625 inches **Keyway Width:** 0.002 inches **Bore Diameter:** 0.627 inches **Bore Length:** 0.625 inches Distance From Center Of Bore To Bottom Of Keyway: 0.315 inches Pitch Diameter: 1.618 inches **Face Width:** 0.105 inches **Design Form:** Plain **Bore Type:** Straight **Metallic Hardness Rating And Location:** 35.0 rockwell c body and 50.0 rockwell c body **Counterbore Feature:** Not included **Lubrication Mode:** No visible means **Keying Facility:** Included **Keying Facility Type:** Keyway **Lightening Hole:** Not included **Teeth Row Quantity: Teeth Quantity Per Row:** 10 **Hardness Rating Test Method:** Rockwell **Teeth Hardness Rating:** Between 35.0 rockwell c and 50.0 rockwell c **Bore Bearing:** Included **Tooth Pitch:**

0.500 inches

NSN 3020-01-204-5879

Sprocket Wheel - Page 2 of 2

Fiig: T353-c



Hub End Outside Diameter And Location:
1.156 inches aa end
Distance From Outside Flange/rim To Hub End And Location:
0.520 inches aa end
Material:
Steel, aisi 1030 or steel, aisi 4140
Material:
Steel comp 1030 or steel comp 4140
Material Specification:
Aisi 1030 assn standard 1st material response and aisi 4140 assn standard 2nd material response
Quantity:
1
Surface Treatment:
Phosphate manganese
Style Designator:
Plain
Surface Treatment:
Phosphate, mil-p-16232, type m, class 2
Shelf Life:
N/a
Unit Of Measure:
Demilitarization:
No