## NSN 3020-01-209-5873

Spur Gear - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/3020-01-209-5873

Body Style:
Plain, solid
Attachment Method:
Clamp
Pitch Diameter:
Between 1.4990 inches and 1.5000 inches
Teeth Quantity:
120
Bore Style:
Plain both ends
Outside Diameter:
0.281 inches
Nominallength:
0.406 inches
Tooth Form:
Standard
Pressure Angle:
20.0000 degrees
Distance Between Body Face And Protruding Hub End:
0.281 inches first end
Face Width:
0.125 inches
Bore Diameter:
0.125 inches both ends
Hub Style Designator:
Split first end
Hub Diameter:
0.188 inches first end
Clamping Surface Length:
0.250 inches first end
Precision Classification:
Quality number 10
End Diameter:
0.249 inches first end
First Step Length:
0.031 inches first end
Special Features:
Hub is also stepped, 0.250 in.Dia, 0.031 in.Lg
Material:
Aluminum alloy 2024

Material Specification:

Qq-a-225/6, t4 federal specification single material response

## NSN 3020-01-209-5873

Spur Gear - Page 2 of 2

A27300

Mil-a-8625 spec.

Mil-std (military Standard):



Surface Treatment:
Anodize
Surface Treatment Specification:
Mil-a-8625, type 1, class 1 military specification single treatment response
Style Designator:
Protruding hub
Shelf Life:
N/a
Unit Of Measure:
Demilitarization:
Yes - demil/mli
Fiig: