# NSN 3020-01-209-5873

Spur Gear - Page 1 of 2



#### **Body Style:**

Plain, solid

#### **Attachment Method:**

Clamp

### **Pitch Diameter:**

Between 1.4990 inches and 1.5000 inches

## **Teeth Quantity:**

120

#### Bore Style:

Plain both ends

## Outside Diameter:

0.281 inches

#### Nominallength:

0.406 inches

#### **Tooth Form:**

Standard

# Pressure Angle:

20.0000 degrees

# Distance Between Body Face And Protruding Hub End:

0.281 inches first end

# Face Width:

0.125 inches

## Bore Diameter:

0.125 inches both ends

### Hub Style Designator:

Split first end

### Hub Diameter:

0.188 inches first end

### Clamping Surface Length:

0.250 inches first end

### **Precision Classification:**

Quality number 10

#### End Diameter:

0.249 inches first end

#### First Step Length:

0.031 inches first end

# **Special Features:**

Hub is also stepped, 0.250 in.Dia, 0.031 in.Lg

# Material:

Aluminum alloy 2024

# Material Specification:

Qq-a-225/6, t4 federal specification single material response



# NSN 3020-01-209-5873

Spur Gear - Page 2 of 2



### Surface Treatment:

Anodize

## Surface Treatment Specification:

Mil-a-8625, type 1, class 1 military specification single treatment response

## Style Designator:

Protruding hub

Shelf Life:

N/a

### Unit Of Measure:

--

# Demilitarization:

Yes - demil/mli

#### Fiig:

A27300

# Mil-std (military Standard):

Mil-a-8625 spec.