## NSN 3020-01-222-1885



Spur Gear - Page 1 of 2 View Online at https://aerobasegroup.com/nsn/3020-01-222-1885 **Body Style:** Plain, solid **Attachment Method:** Mounting hole Pitch Diameter: 0.7222 inches **Teeth Quantity:** 52 **Bore Style:** Plain both ends **Mounting Hole Thread Series Designator:** Unc transversely through hub, first end Mounting Hole Thready Qty Per Inch (tpi): 56 transversely through hub, first end **Mounting Hole Thread Size:** 0.086 inches transversely through hub, first end **Mounting Hole Type And Quantity:** 1 threaded transversely through hub, first end **Outside Diameter:** 0.750 inches Nominallength: 0.3750 inches **Tooth Form:** Standard **Pressure Angle:** 20.0000 degrees **Distance Between Body Face And Protruding Hub End:** 0.220 inches first end **Face Width:** 0.1550 inches **Bore Diameter:** 0.188 inches both ends **Hub Style Designator:** Pinned first end **Hub Diameter:** 0.375 inches first end **Precision Classification:** Quality number 12 Material: Steel comp 416se

**Material Specification:** 

Ams 5610 assn standard single material response

## NSN 3020-01-222-1885

Spur Gear - Page 2 of 2



$\overline{}$			-			
<b>~</b> I	ırfa	ഫ	ırc	natr	nΔn	

Passivate

**Style Designator:** 

Protruding hub

Shelf Life:

N/a

**Unit Of Measure:** 

--

Demilitarization:

Yes - demil/mli

Fiig:

A27300