## NSN 3020-01-230-0139

Spur Gear - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/3020-01-230-0139

| Body Style:   |
|---|
| Plain, solid  |
| Pitch Diameter:   |
| 3.7500 inches   |
| Teeth Quantity:   |
| 60  |
| Bore Style:   |
| Plain both ends   |
| Hardness Rating:  |
| 30.0 rockwell c and 38.0 rockwell c                     |
| Outside Diameter:                                       |
| 3.850 inches  |
| Tooth Form:   |
| Standard  |
| Flange Diameter:  |
| 2.920 inches  |
| Pilot Length:   |
| 0.362 inches  |
| Pressure Angle:   |
| 20.0000 degrees   |
| Flange Thickness:                                       |
| 0.249 inches  |
| Face Width:   |
| 0.200 inches  |
| Bore Diameter:  |
| 0.751 inches both ends                                  |
| Bore Depth:   |
| 1.791 inches both ends                                  |
| Distance Between Outer Body Face And Inner Flange Face: |
| 1.180 inches  |
| Hub Diameter:   |
| 1.000 inches between body and flange                    |
| Precision Classification:                               |
| Quality number 8  |
| Pilot Diameter:   |
| 1.498 inches  |
| Material:   |
| Steel   |
| Surface Treatment:                                      |
| Phosphate   |
| Style Designator:                                       |

Flanged end with pilot

## NSN 3020-01-230-0139

Spur Gear - Page 2 of 2



| _ |   |    | • |    |    |
|---|---|----|---|----|----|
| • | n | ο. | • | 18 | e: |
|   |   |    |   |    |    |

N/a

**Unit Of Measure:** 

--

Demilitarization:

No

Fiig:

A27300