NSN 3020-01-230-5030

Spur Gear - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/3020-01-230-5030 **Body Style:** Plain, solid **Attachment Method:** Mounting hole Pitch Diameter: 4.8500 inches **Teeth Quantity:** 97 **Bore Style:** Plain both ends **Mounting Hole Thread Series Designator:** Unc transversely through hub, first end Mounting Hole Thready Qty Per Inch (tpi): 32 transversely through hub, first end **Mounting Hole Thread Size:** 0.190 inches transversely through hub, first end **Mounting Hole Type And Quantity:** 1 threaded transversely through hub, first end **Outside Diameter:** 4.934 inches Nominallength: 0.875 inches **Tooth Form:** Standard **Pressure Angle:** 20.0000 degrees **Distance Between Body Face And Protruding Hub End:** 0.500 inches first end **Face Width:** 0.375 inches **Bore Diameter:** 0.500 inches both ends **Bore Depth:** 0.875 inches both ends **Hub Style Designator:** Pinned first end **Hub Diameter:** 1.250 inches first end **Special Features:** Distance from first end of hub to center of tapped hole 0.250 nom. In. Material:

Steel

NSN 3020-01-230-5030 Spur Gear - Page 2 of 2

Fiig: A27300



Surface Treatment:
Cadmium
Surface Treatment Specification:
Qq-p-416, type 1, cl 2 federal specification single treatment response
Style Designator:
Protruding hub
Shelf Life:
N/a
Unit Of Measure:
Demilitarization:
No