## NSN 3020-01-230-5030

Spur Gear - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/3020-01-230-5030

**Body Style:** Plain, solid **Attachment Method:** Mounting hole **Pitch Diameter:** 4.8500 inches **Teeth Quantity:** 97 **Bore Style:** Plain both ends Mounting Hole Thread Series Designator: Unc transversely through hub, first end Mounting Hole Thready Qty Per Inch (tpi): 32 transversely through hub, first end Mounting Hole Thread Size: 0.190 inches transversely through hub, first end Mounting Hole Type And Quantity: 1 threaded transversely through hub, first end **Outside Diameter:** 4.934 inches Nominallength: 0.875 inches **Tooth Form:** Standard **Pressure Angle:** 20.0000 degrees **Distance Between Body Face And Protruding Hub End:** 0.500 inches first end Face Width: 0.375 inches **Bore Diameter:** 0.500 inches both ends Bore Depth: 0.875 inches both ends Hub Style Designator: Pinned first end Hub Diameter: 1.250 inches first end **Special Features:** Distance from first end of hub to center of tapped hole 0.250 nom. In. Material: Steel

# NSN 3020-01-230-5030

Spur Gear - Page 2 of 2



Surface Treatment:

Cadmium

### Surface Treatment Specification:

Qq-p-416, type 1, cl 2 federal specification single treatment response

#### Style Designator:

Protruding hub

Shelf Life:

N/a

Unit Of Measure:

--

#### Demilitarization:

No

### Fiig:

A27300