NSN 3020-01-230-5031

Spur Gear - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/3020-01-230-5031

| Body Style: |
|--|
| Plain, solid |
| Pitch Diameter: |
| 3.2500 inches |
| Teeth Quantity: |
| 104 |
| Bore Style: |
| 10a w/ keyway both ends |
| Outside Diameter: |
| 3.306 inches |
| Nominallength: |
| 0.370 inches |
| Tooth Form: |
| Standard |
| Pressure Angle: |
| 20.0000 degrees |
| Distance Between Body Face And Protruding Hub End: |
| 0.085 inches both ends |
| Face Width: |
| 0.203 inches |
| Bore Diameter: |
| 0.626 inches both ends |
| Bore Depth: |
| 0.370 inches both ends |
| Keyway Width: |
| 0.127 inches both ends |
| Distance From Bore Center To Keyway Bottom: |
| 0.375 inches both ends |
| Hub Style Designator: |
| Plain second end |
| Hub Diameter: |
| 0.781 inches first end |
| Precision Classification: |
| Quality number 8 |
| Material: |
| Steel |
| Surface Treatment: |
| Phosphate |
| Style Designator: |
| Protruding hubs |
| Shelf Life: |
| N/a |

NSN 3020-01-230-5031 Spur Gear - Page 2 of 2



| ı | In | it I | Of | · M | دما | e i | ıre: |
|---|----|------|----|-----|-----|-----|------|
| ι | JΝ | II ' | ωı | IV | еа | SU | ıre: |

Demilitarization:

No

Fiig:

A27300